

RATINGS / APPROVALS

250°C - 300 Volts - UL Style 5257 / CSA AWM I A/B FT I

250°C - 600 Volts - UL Style 5251/5256 / CSA AWM I A/B FT I

CONSTRUCTION

Conductors

24 AWG - 10 AWG (300V)

24 AWG - 4/0 AWG (600V)

Stranded nickel-plated copper - 2%

(Other conductor materials available)

Insulating System

PTFE Tape with glass serve

Outer Covering

Braided fiberglass with a high temperature finish


Standard Color Coding

Natural and Solid Colors

Colored Tracers

CHARACTERISTICS

- Excellent cut and strip characteristics making it ideal for high volume manufacturing and assembly.
- Tough treated outer glass braid and fiberglass servings permit the product to withstand repeated flexing and severe mechanical abuse.
- Moisture resistant
- Resists pushback and braid fray
- Flexible



COPYRIGHT

This document is protected under copyright law and is the property of Radix Wire and Cable. Data contained herein is confidential to Radix Wire and Cable and this document and/or any part of the data contained herein may not be copied, duplicated or released for manufacturing or sale of equipment outside of Radix Wire and Cable or any affiliates without the prior written authorization of Radix Wire & Cable.

SPECIFICATIONS

TGGT 250 HIGH-TEMPERATURE LEAD WIRE

TGGT 250C/300V

Part No.	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt. (lbs/Mft)	Wgt (kg/km)	Min. Bend Radius (in)	UL	CSA
DAT24P007	24	7	0.064	1.63	4	5.74	0.51	5257	AWM I A/B FT I
DAT22P007	22	7	0.068	1.73	5	7.26	0.54	5257	AWM I A/B FT I
DAT20P007	20	7	0.072	1.83	6	9.21	0.58	5257	AWM I A/B FT I
DAT18P019	18	19	0.079	2.01	8	12.13	0.63	5257	AWM I A/B FT I
DAT16P026	16	26	0.099	2.51	13	19.81	0.79	5257	AWM I A/B FT I
DAT14P041	14	41	0.114	2.90	19	27.98	0.91	5257	AWM I A/B FT I
DAT12P065	12	65	0.132	3.35	28	41.31	1.06	5257	AWM I A/B FT I
DAT10P105	10	105	0.157	3.99	42	61.94	1.26	5257	AWM I A/B FT I

TGGT 250C/600V

Part No.	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt. (lbs/Mft)	Wgt (kg/km)	Min. Bend Radius (in)	UL	CSA
DBT24P007	24	7	0.068	1.73	4	6.43	0.54	5256	AWM I A/B FT I
DBT22P007	22	7	0.074	1.88	6	8.20	0.59	5256	AWM I A/B FT I
DBT20P007	20	7	0.085	2.16	7	10.95	0.68	5256	AWM I A/B FT I
DBT18P019	18	19	0.090	2.29	9	14.06	0.72	5256	AWM I A/B FT I
DBT16P026	16	26	0.107	2.72	14	21.30	0.86	5256	AWM I A/B FT I
DBT14P041	14	41	0.120	3.05	20	29.65	0.96	5256	AWM I A/B FT I
DBT12P065	12	65	0.139	3.53	29	43.23	1.11	5256	AWM I A/B FT I
DBT10P105	10	105	0.164	4.17	43	64.37	1.31	5256	AWM I A/B FT I
DBT08P133	8	133	0.211	5.36	66	98.09	1.69	5256	AWM I A/B FT I
DBT06P133	6	133	0.257	6.53	99	147.19	2.06	5256	AWM I A/B FT I
DBT04P133	4	133	0.335	8.51	164	244.07	2.68	5256	AWM I A/B FT I
DBT02P133	2	133	0.401	10.19	248	369.08	3.21	5256	AWM I A/B FT I
AITX1P259	1/0	259	0.531	13.49	404	601.25	4.25	5251	AWM I A/B FT I
AITX2P259	2/0	259	0.582	14.78	499	742.63	4.66	5251	AWM I A/B FT I
AITX3P259	3/0	259	0.639	16.23	617	918.24	5.11	5251	AWM I A/B FT I
AITX4P259	4/0	259	0.702	17.83	762	1134.04	5.62	5251	AWM I A/B FT I

Standard conductor: Nickel Plated Copper - 2%
Consult factory for alternative conductor and stranding options.



WIRE & CABLE
EST. 1944

All dimensions listed above are nominal
Compliance: UL Listed File No. E22244. CSA Certified File No. LL13427 or LL80670
Information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact the Radix factory for dimensional verification. Information herein is believed to be accurate as of publication date; however, if an error exists it is unintentional and Radix Wire & Cable is not responsible for any claim traceable to such error.

Radix Wire & Cable
26000 Lakeland Boulevard, Euclid, OH 44132
Tel: 216 731-9191 • Fax: 216 731-7082
www.radix-wire.com

Use or disclosure of data contained on this sheet is subject to the restrictions on the title page.