

200C/1KV • 200C/3KV
200C/5KV • 200C/8KV
200C/15KV

Super J High-Volt 200

HIGH TEMPERATURE MOTOR LEAD WIRE

RATINGS / APPROVALS

200°C - 1KV - UL 3644 / CSA AWM I A/B FT2
200°C - 3KV - UL 30056
200°C - 5KV - UL 30057
200°C - 8KV - UL 30058
200°C - 15KV - UL 30081

CONSTRUCTION

Conductors

24 AWG - 750 MCM (1kV)
22 AWG - 350 MCM (3kV)
18 AWG - 350 MCM (5kV, 8kV)
18 AWG - 350 MCM (15kV)

Stranded tinned copper or nickel-plated copper

*Consult factory for alternative conductor and stranding options.

Insulating System

Super J Extruded Silicone Rubber

Standard Color: Gray

Also available in colors and stripes

CHARACTERISTICS

- Superior Abrasion and Cut-Through Resistance
- Superior flexibility
- LSZH: Low Smoke, Zero Halogen
- Silicone formulation suitable for UV, ozone & moisture exposure.
- Not suitable for immersed applications.
- Suitable for applications to -60°C

Exceptional replacement for High Voltage EPDM motor lead wire.



Stranded Tinned Copper
or Nickel-Plated Copper

Super J Silicone Rubber

COPYRIGHT

This document is protected under copyright law and is the property of Radix Wire and Cable. Data contained herein is confidential to Radix Wire and Cable and this document and/or any part of the data contained herein may not be copied, duplicated or released for manufacturing or sale of equipment outside of Radix Wire and Cable or any affiliates without the prior written authorization of Radix Wire & Cable.

03-2-2023

Radix[™]
WIRE & CABLE

SPECIFICATIONS

Super J High-Volt 200

HIGH TEMPERATURE MOTOR LEAD WIRE

SUPER J HIGH-VOLT 200°C/1000V

Part No.	Temp Rating	Voltage Rating	Awg. Size	# Strands	Final O.D. (in)	Final O.D. (mm)	Wgt. (lbs/Mft)	Wgt. (kg/km)	Min. Bend Radius (in)	UL	CSA
NGJ24P007	200C	1000V	24 NPC 2%	7	0.086	2.18	4.16	6.19	0.69	3644	AWM I A/B FT2
NGJ22P007	200C	1000V	22 NPC 2%	7	0.092	2.34	5.34	7.95	0.74	3644	AWM I A/B FT2
NGJ20P007	200C	1000V	20 NPC 2%	7	0.099	2.51	6.69	9.96	0.79	3644	AWM I A/B FT2
NGJ18T007	200C	1000V	18	7	0.108	2.74	8.91	13.26	0.86	3644	AWM I A/B FT2
NGJ16T007	200C	1000V	16	7	0.120	3.05	12.49	18.59	0.96	3644	AWM I A/B FT2
NGJ14T007	200C	1000V	14	7	0.133	3.38	17.10	25.45	1.06	3644	AWM I A/B FT2
NGJ12T019	200C	1000V	12	19	0.150	3.81	26.24	39.05	1.20	3644	AWM I A/B FT2
NGJ10T019	200C	1000V	10	19	0.173	4.39	39.31	58.50	1.38	3644	AWM I A/B FT2
NGJ08T061	200C	1000V	8	61	0.234	5.94	76.10	113.25	1.87	3644	AWM I A/B FT2
NGJ06T084	200C	1000V	6	84	0.337	8.56	111.18	165.46	2.70	3644	AWM I A/B FT2
NGJ04T133	200C	1000V	4	133	0.371	9.42	152.31	226.67	2.97	3644	AWM I A/B FT2
NGJ02T259	200C	1000V	2	259	0.436	11.07	230.75	343.41	3.49	3644	AWM I A/B FT2
NGJ01T259	200C	1000V	1	259	0.507	12.88	300.27	446.87	4.06	3644	AWM I A/B FT2
NGJX1T259	200C	1000V	1/0	259	0.562	14.27	386.63	575.40	4.50	3644	AWM I A/B FT2
NGJX2T259	200C	1000V	2/0	259	0.608	15.44	475.03	706.96	4.86	3644	AWM I A/B FT2
NGJX3T259	200C	1000V	3/0	259	0.657	16.69	585.23	870.96	5.26	3644	AWM I A/B FT2
NGJX4T259	200C	1000V	4/0	259	0.717	18.21	724.05	1077.56	5.74	3644	AWM I A/B FT2
NGJ25T427	200C	1000V	250 MCM	427	0.816	20.73	858.19	1277.19	6.53	3644	AWM I A/B FT2
NGJ35T427	200C	1000V	350 MCM	427	0.926	23.52	1171.88	1744.03	7.41	3644	AWM I A/B FT2
NGJ50T427	200C	1000V	500 MCM	427	1.056	26.82	1606.60	2391.00	8.45	3644	AWM I A/B FT2
NGJ75T703	200C	1000V	750 MCM	703	1.318	33.48	2539.63	3779.57	10.54	3644	AWM I A/B FT2

SUPER J HIGH-VOLT 200°C/3000V

Part No.	Temp Rating	Voltage Rating	Awg. Size	# Strands	Final O.D. (in)	Final O.D. (mm)	Wgt. (lbs/Mft)	Wgt. (kg/km)	Min. Bend Radius (in)	UL	CSA
MEJ22P007	200C	3000V	22 NPC 2%	7	0.144	3.66	10.40	15.48	1.15	30056	N/A
MEJ20P007	200C	3000V	20 NPC 2%	7	0.151	3.84	12.03	17.90	1.21	30056	N/A
MEJ18T007	200C	3000V	18	7	0.160	4.06	14.64	21.79	1.28	30056	N/A
MEJ16T007	200C	3000V	16	7	0.172	4.37	18.73	27.87	1.38	30056	N/A
MEJ14T007	200C	3000V	14	7	0.185	4.70	23.91	35.58	1.48	30056	N/A
MEJ12T019	200C	3000V	12	19	0.202	5.13	33.78	50.27	1.62	30056	N/A
MEJ10T019	200C	3000V	10	19	0.309	7.85	66.32	98.70	2.47	30056	N/A
MEJ08T061	200C	3000V	8	61	0.338	8.59	91.78	136.59	2.70	30056	N/A
MEJ06T084	200C	3000V	6	84	0.410	10.41	134.09	199.56	3.28	30056	N/A
MEJ04T133	200C	3000V	4	133	0.444	11.28	177.46	264.10	3.55	30056	N/A
MEJ02T259	200C	3000V	2	259	0.509	12.93	259.80	386.64	4.07	30056	N/A
MEJ01T259	200C	3000V	1	259	0.544	13.82	313.74	466.92	4.35	30056	N/A
MEJX1T259	200C	3000V	1/0	259	0.599	15.21	395.71	588.91	4.79	30056	N/A
MEJX2T259	200C	3000V	2/0	259	0.645	16.38	484.88	721.62	5.16	30056	N/A
MEJX3T259	200C	3000V	3/0	259	0.694	17.63	595.76	886.63	5.55	30056	N/A
MEJX4T259	200C	3000V	4/0	259	0.804	20.42	767.76	1142.61	6.43	30056	N/A
MEJ25T427	200C	3000V	250 MCM	427	0.869	22.07	896.53	1334.25	6.95	30056	N/A
MEJ35T427	200C	3000V	350 MCM	427	0.979	24.87	1215.00	1808.21	7.83	30056	N/A

SPECIFICATIONS

Super J High-Volt 200

HIGH TEMPERATURE MOTOR LEAD WIRE

SUPER J HIGH-VOLT 200°C/5000V

Part No.	Temp Rating	Voltage Rating	Awg. Size	# Strands	Final O.D. (in)	Final O.D. (mm)	Wgt. (lbs/Mft)	Wgt. (kg/km)	Min. Bend Radius (in)	UL	CSA
MFJ18T007	200C	5000V	18	7	0.202	5.13	20.89	31.09	1.62	30057	N/A
MFJ16T007	200C	5000V	16	7	0.214	5.44	25.39	37.79	1.71	30057	N/A
MFJ14T007	200C	5000V	14	7	0.227	5.77	31.04	46.19	1.82	30057	N/A
MFJ12T019	200C	5000V	12	19	0.244	6.20	41.50	61.76	1.95	30057	N/A
MFJ10T019	200C	5000V	10	19	0.359	9.12	80.08	119.18	2.87	30057	N/A
MFJ08T061	200C	5000V	8	61	0.388	9.86	106.74	158.85	3.10	30057	N/A
MFJ06T084	200C	5000V	6	84	0.460	11.68	152.00	226.21	3.68	30057	N/A
MFJ04T133	200C	5000V	4	133	0.494	12.55	196.78	292.86	3.95	30057	N/A
MFJ02T259	200C	5000V	2	259	0.559	14.20	281.80	419.39	4.47	30057	N/A
MFJ01T259	200C	5000V	1	259	0.594	15.09	337.17	501.79	4.75	30057	N/A
MFJX1T259	200C	5000V	1/0	259	0.649	16.48	421.41	627.16	5.19	30057	N/A
MFJX2T259	200C	5000V	2/0	259	0.695	17.65	512.48	762.69	5.56	30057	N/A
MFJX3T259	200C	5000V	3/0	259	0.744	18.90	625.38	930.71	5.95	30057	N/A
MFJX4T259	200C	5000V	4/0	259	0.846	21.49	796.30	1185.08	6.77	30057	N/A
MFJ25T427	200C	5000V	250 MCM	427	0.911	23.14	927.32	1380.07	7.29	30057	N/A
MFJ35T427	200C	5000V	350 MCM	427	1.021	25.93	1249.61	1859.72	8.17	30057	N/A

SUPER J HIGH-VOLT 200°C/8000V

Part No.	Temp Rating	Voltage Rating	Awg. Size	# Strands	Final O.D. (in)	Final O.D. (mm)	Wgt. (lbs/Mft)	Wgt. (kg/km)	Min. Bend Radius (in)	UL	CSA
MGJ18T007	200C	8000V	18	7	0.244	6.20	28.59	42.55	1.95	30058	N/A
MGJ16T007	200C	8000V	16	7	0.256	6.50	33.51	49.87	2.05	30058	N/A
MGJ14T007	200C	8000V	14	7	0.269	6.83	39.63	58.98	2.15	30058	N/A
MGJ12T019	200C	8000V	12	19	0.286	7.26	50.67	75.41	2.29	30058	N/A
MGJ10T019	200C	8000V	10	19	0.381	9.68	86.79	129.16	3.05	30058	N/A
MGJ08T061	200C	8000V	8	61	0.410	10.41	113.97	169.61	3.28	30058	N/A
MGJ06T084	200C	8000V	6	84	0.481	12.22	159.70	237.67	3.85	30058	N/A
MGJ04T133	200C	8000V	4	133	0.516	13.11	205.93	306.47	4.13	30058	N/A
MGJ02T259	200C	8000V	2	259	0.581	14.76	292.12	434.74	4.65	30058	N/A
MGJ01T259	200C	8000V	1	259	0.616	15.65	348.14	518.11	4.93	30058	N/A
MGJX1T259	200C	8000V	1/0	259	0.671	17.04	433.37	644.96	5.37	30058	N/A
MGJX2T259	200C	8000V	2/0	259	0.717	18.21	525.28	781.74	5.74	30058	N/A
MGJX3T259	200C	8000V	3/0	259	0.766	19.46	639.06	951.07	6.13	30058	N/A
MGJX4T259	200C	8000V	4/0	259	0.896	22.76	832.18	1238.48	7.17	30058	N/A
MGJ25T427	200C	8000V	250 MCM	427	0.961	24.41	965.88	1437.46	7.69	30058	N/A
MGJ35T427	200C	8000V	350 MCM	427	1.071	27.20	1292.69	1923.83	8.57	30058	N/A

SPECIFICATIONS

Super J High-Volt 200 HIGH TEMPERATURE MOTOR LEAD WIRE

SUPER J HIGH-VOLT 200°C/15000V

Part No.	Temp Rating	Voltage Rating	Awg. Size	# Strands	Final O.D. (in)	Final O.D. (mm)	Wgt. (lbs/Mft)	Wgt. (kg/km)	Min. Bend Radius (in)	UL	CSA
MHJ18T007	200C	15000V	18	7	0.366	9.30	59.21	88.12	2.93	3008I	N/A
MHJ16T007	200C	15000V	16	7	0.378	9.60	65.34	97.24	3.02	3008I	N/A
MHJ14T007	200C	15000V	14	7	0.391	9.93	72.80	108.34	3.13	3008I	N/A
MHJ12T019	200C	15000V	12	19	0.408	10.36	85.55	127.32	3.26	3008I	N/A
MHJ10T019	200C	15000V	10	19	0.431	10.95	103.52	154.06	3.45	3008I	N/A
MHJ08T061	200C	15000V	8	61	0.460	11.68	131.89	196.29	3.68	3008I	N/A
MHJ06T084	200C	15000V	6	84	0.531	13.49	180.54	268.69	4.25	3008I	N/A
MHJ04T133	200C	15000V	4	133	0.566	14.38	228.21	339.63	4.53	3008I	N/A
MHJ02T259	200C	15000V	2	259	0.631	16.03	317.08	471.90	5.05	3008I	N/A
MHJ01T259	200C	15000V	1	259	0.666	16.92	374.54	557.40	5.33	3008I	N/A
MHJX1T259	200C	15000V	1/0	259	0.791	20.09	505.64	752.51	6.33	3008I	N/A
MHJX2T259	200C	15000V	2/0	259	0.837	21.26	602.09	896.05	6.70	3008I	N/A
MHJX3T259	200C	15000V	3/0	259	0.886	22.50	720.72	1072.60	7.09	3008I	N/A
MHJX4T259	200C	15000V	4/0	259	0.946	24.03	870.12	1294.94	7.57	3008I	N/A
MHJ25T427	200C	15000V	250 MCM	427	1.081	27.46	1066.82	1587.68	8.65	3008I	N/A
MHJ35T427	200C	15000V	350 MCM	427	1.191	30.25	1404.51	2090.24	9.53	3008I	N/A

Standard conductor: Tinned Copper or Nickel Plated Copper (2%) as designated

All dimensions listed above are nominal. Consult factory for alternate conductor and stranding options

Check the Website (www.radix-wire.com) or contact Sales for additional cable configurations not listed.

Information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact the Radix factory for dimensional verification. Information herein is believed to be accurate as of publication date; however, if an error exists it is unintentional and Radix Wire & Cable is not responsible for any claim traceable to such error.

Use or disclosure of data contained on this sheet is subject to the restrictions on the title page.

Radix[™]
WIRE & CABLE