

# BRAIDED SILICONE 250

HIGH-TEMPERATURE LEAD WIRE

250C/300V and 250C/600V

## RATINGS / APPROVALS

250°C - 300 Volts - UL Style 3254 / CSA AWM I A/B FT2

250°C - 600 Volts - UL Style 3252 / CSA AWM I A/B FT2

RoHS Compliant

## CONSTRUCTION

Conductors

24 AWG - 12 AWG (300 Volts)

22 AWG - 10 AWG (600 Volts)

Stranded nickel-plated copper

(Other conductor materials available)

Insulating System

Extruded Silicone Rubber with Fiberglass Braid

Outer Covering


Braided fiberglass with a high temperature finish

Standard Color Coding

Available in Colors or Striped Combinations

## CHARACTERISTICS

- Silicone formulations suitable for UV, ozone, moisture exposure.
- Not suited for immersed applications
- Suitable for applications to -60°C.
- Silicone Rubber in extreme environments, exceeding 250°C, leaves a non-conductive ash and retains excellent insulation properties.
- Flexible
- PFAS-free



### COPYRIGHT

This document is protected under copyright law and is the property of Radix Wire and Cable. Data contained herein is confidential to Radix Wire and Cable and this document and/or any part of the data contained herein may not be copied, duplicated or released for manufacturing or sale of equipment outside of Radix Wire and Cable or any affiliates without the prior written authorization of Radix Wire & Cable.

2-14-2025

**Radix**<sup>™</sup>  
WIRE & CABLE

# SPECIFICATIONS

# BRAIDED SILICONE 250

## HIGH-TEMPERATURE LEAD WIRE

### BRAIDED SILICONE 250C/300V

Part No.	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt. (lbs/Mft)	Wgt (kg/km)	Min. Bend Radius (in)	UL	CSA
EGM22P007	22	7	0.106	2.69	7	8.93	0.85	3254	AWM I A/B FT2
EGM20P007	20	7	0.112	2.84	8	10.05	0.90	3254	AWM I A/B FT2
EGM18P019	18	19	0.118	3.00	9	13.39	0.94	3254	AWM I A/B FT2
EGM16P026	16	26	0.134	3.40	13	18.96	1.07	3254	AWM I A/B FT2
EGM14P041	14	41	0.149	3.78	18	27.03	1.19	3254	AWM I A/B FT2
EGM12P065	12	65	0.168	4.27	30	44.85	1.34	3254	AWM I A/B FT2

### BRAIDED SILICONE 250C/600V

Part No.	Awg. Size	# Strands	Outer Dia. inches	Outer Dia. mm	Wgt. (lbs/Mft)	Wgt (kg/km)	Min. Bend Radius (in)	UL	CSA
EIM22P007	22	7	0.106	2.69	7	10.45	0.85	3252	AWM I A/B FT2
EIM20P007	20	7	0.113	2.87	8	12.55	0.90	3252	AWM I A/B FT2
EIM18P019	18	19	0.116	2.95	10	15.34	0.93	3252	AWM I A/B FT2
EIM16P026	16	26	0.127	3.23	14	21.15	1.02	3252	AWM I A/B FT2
EIM14P041	14	41	0.142	3.61	20	29.54	1.14	3252	AWM I A/B FT2
EIM12P065	12	65	0.166	4.22	29	43.71	1.33	3252	AWM I A/B FT2
EIM10P105	10	105	0.191	4.85	43	64.57	1.53	3252	AWM I A/B FT2

Standard conductor: Nickel Plated Copper - 2%  
Consult factory for alternative conductor and stranding options.

All dimensions listed above are nominal  
Compliance: UL Listed File No. E22244. CSA Certified File No. LL13427 or LL80670  
Information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact the Radix factory for dimensional verification. Information herein is believed to be accurate as of publication date; however, if an error exists it is unintentional and Radix Wire & Cable is not responsible for any claim traceable to such error.

Use or disclosure of data contained on this sheet is subject to the restrictions on the title page.

**Radix**<sup>™</sup>  
WIRE & CABLE

www.Radix-Wire.com